

OT16FT3



General Information

| | |
|-------------------------------|---|
| Extended Product Type: | OT16FT3 |
| Product ID: | 1SCA104838R1001 |
| EAN: | 6417019389820 |
| Catalog Description: | OT16FT3 Switch-disconnector |
| Long Description: | Front operated switch-disconnector. Types OT 16...125 include protected terminal clamps, IP 20. |

Categories

Products » Low Voltage Products and Systems » Switches » Switch Disconnectors

Ordering

| | |
|--------------------------------|---------------|
| EAN: | 6417019389820 |
| Minimum Order Quantity: | 10 piece |
| Customs Tariff Number: | 85365080 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width: | 43 mm |
| Product Net Height: | 54 mm |
| Product Net Depth: | 52 mm |
| Product Net Weight: | 0.13 kg |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 63 mm |
| Package Level 1 Height: | 54 mm |
| Package Level 1 Length: | 65 mm |
| Package Level 1 Gross Weight: | 0.13 kg |
| Package Level 1 EAN: | 6417019389820 |

Environmental

| | |
|---------------------|---|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q3 |
|---------------------|---|

Technical UL/CSA

| | |
|-----------------------------------|--|
| Ampere Rating UL/CSA: | 16 A |
| Horse Power Rating UL/CSA: | acc. to UL 200V 3 Hp acc. to UL 208V 3 Hp acc. to UL 240V 5 Hp acc. to UL 480V 10 Hp acc. to UL 600V 10 Hp |

Additional Information

| | |
|--|-------------------------------|
| Cable Cross-Section: | 0.75...10 mm ² |
| Conventional Free-air Thermal Current (I_{th}): | q=40°C 25 A |
| Conventional Thermal Current (I_{the}): | Fully Enclosed 25 A |
| Earthing Switch Type: | No Additional Type |
| Handle Type: | None |
| IIT Publishing Status: | Level 0 - Information enabled |

| | |
|--|---|
| Includes: | None |
| Mounting Type: | Door Mounting |
| Number of Poles: | 3 |
| Operating Mechanism: | Mechanism on top of the switch |
| Operating Mode: | Front Operated |
| Order Multiple: | 10 piece |
| Pollution Degree: | 3 |
| Position of Line Terminals: | Top in - bottom out |
| Power Loss: | Per Pole 0.3 W |
| Product Main Type: | OT |
| Product Name: | Switch-disconnectors |
| Rated Impulse Withstand Voltage (U_{imp}): | 8 kV |
| Rated Insulation Voltage (U_i): | 750 V |
| Rated Operational Current AC-21A (I_e): | (380 ... 415V) 16 A (500V) 16 A (690V) 10 A |
| Rated Operational Current AC-22A (I_e): | (500 V) 16 A (380 ... 415 V) 16 A (690 V) 16 A |
| Rated Operational Current AC-23A (I_e): | (500 V) 16 A (690 V) 16 A (380 ... 415 V) 16 A |
| Rated Operational Power AC-23A (P_e): | (220 ... 240V) 3 kW (400V) 7.5 kW (415V) 7.5 kW (500V) 7.5 kW (690V) 7.5 kW |
| Rated Operational Voltage: | 750 V |
| Rated Short-time Withstand Current (I_{cw}): | for 1.0s 0.5 kiloampere rms |
| Special Functions: | No |
| Standards: | IEC |
| Terminal Type: | Screw Terminals |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| Declaration of Conformity - CE: | 1SCC301166D0201 |
| RoHS Information: | 1SCC301183D0201 |

Classifications

| | |
|------------------------------------|--------------------------------|
| E-nummer: | 3170944 |
| ETIM 5.0: | EC000216 - Switch disconnecter |
| Object Classification Code: | Q |

