

S1-M1-25



General Information

Extended Product Type:	S1-M1-25
Product ID:	1SAM201907R1101
EAN:	4013614400803
Catalog Description:	S1-M1-25 3-Phase Power Infeed Block
Long Description:	S1-M1-25 3-phase power infeed block Flat, for MS116 / MS132, 25mm ²

Categories

Products » Low Voltage Products and Systems » Control Products » Manual Motor Starters » Manual Motor Starters Accessories

Ordering

EAN:	4013614400803
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369010

Container Information

Package Level 1 Width:	80.0 mm
Package Level 1 Length:	120.0 mm
Package Level 1 Height:	46.0 mm
Package Level 1 Gross Weight:	0.409 kg
Package Level 1 EAN:	4013614488184
Package Level 1 Units:	10 piece

Dimensions

Product Net Width:	44.0 mm
Product Net Height:	38.0 mm
Product Net Depth:	25.5 mm
Product Net Weight:	0.038 kg

Technical

Rated Operational Voltage:	690 V
Rated Operational Current (I_e):	65 A
Degree of Protection:	IP20
Connecting Capacity-Main Circuit:	Rigid 1x 6 ... 25 mm ² Flexible 1x 6 ... 16 mm ²
Tightening Torque:	Main Circuit 2.5 N·m
Wire Stripping Length:	Main Circuit 10 mm
Recommended Screw Driver:	Pozidriv 2 M3.5
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Product Name:	3-Phase Power Infeed Block
Suitable For:	MS116 MS132
Suitable for Product Class:	Manual Motor Starters

Environmental

Ambient Air Temperature:	Operation -25 +70 °C Storage -50 ...+80 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Ampere Rating UL/CSA:	65 A
Connecting Capacity-Main Circuit UL/CSA:	Stranded 1/2x 10 ... 4 AWG Flexible 1/2x 10 ... 6 AWG
Tightening Torque UL/CSA:	Main Circuit 22 in-lb

Certificates and Declarations (Document Number)

cUL Certificate:	1SAA963001-1701
Declaration of Conformity - CE:	1SAD938509-0056
GOST Certificate:	1SAA937000-2703
RoHS Information:	1SAA963003-4402
UL Certificate:	1SAA963001-1602

Classifications

E-nummer:	3111687
Object Classification Code:	X
UNSPSC:	39120000

