

## Optical element - PSD-S OE LED YE - 2700122

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




LED permanent light element, 24 V AC/DC, yellow

### Your advantages

- ✓ Tool-free element changeover
- ✓ Can be freely combined
- ✓ High light and color intensity
- ✓ Minimum LED service life of 50,000 h
- ✓ Low power consumption
- ✓ IP65 degree of protection

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 491167
GTIN	4046356491167
Weight per Piece (excluding packing)	72.600 g
Custom tariff number	85318070
Country of origin	Germany

### Technical data

#### Dimensions

Diameter	70 mm
Height	65.5 mm

#### Ambient conditions

Ambient temperature (operation)	-30 °C ... 50 °C
Degree of protection	IP65, when installed or with cover

#### General

Material	Polycarbonate PC
----------	------------------

# Optical element - PSD-S OE LED YE - 2700122

## Technical data

### General

Calotte color	yellow
Weight	58 g
Mounting position	any
Assembly instructions	Rubber seal pre-installed for each element

### Electrical data

Input voltage	24 V AC/DC
Maximum inrush current	max. 500 mA
Current consumption	30 mA
Service life, electrical	max. 100,000 h
Operating time	100 %
Optical signal type	Permanent light

### Approvals / conformities

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---

### Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---


### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Drawings

# Optical element - PSD-S OE LED YE - 2700122

Dimensional drawing



## Classifications

### eCl@ss

eCl@ss 4.0	27143200
eCl@ss 4.1	27143200
eCl@ss 5.0	27371200
eCl@ss 5.1	27371200
eCl@ss 6.0	27371200
eCl@ss 7.0	27371220
eCl@ss 8.0	27371220
eCl@ss 9.0	27371220

### ETIM

ETIM 3.0	EC000232
ETIM 4.0	EC000232
ETIM 5.0	EC000232

# Optical element - PSD-S OE LED YE - 2700122

## Classifications

### ETIM

ETIM 6.0	EC000232
ETIM 7.0	EC000232

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	46171604
UNSPSC 18.0	46171604
UNSPSC 19.0	46171604
UNSPSC 20.0	46171604
UNSPSC 21.0	46171604

## Approvals


### Approvals


#### Approvals

UL Listed / cUL Listed / EAC / EAC / cULus Listed

#### Ex Approvals

### Approval details

UL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 123528
-----------	---	---	---------------

cUL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 123528
------------	---	---	---------------

EAC		EAC-Zulassung
-----	---	---------------

EAC		RU *- DE.A*30.B.00237
-----	---	--------------------------

## Optical element - PSD-S OE LED YE - 2700122

### Approvals

cULus Listed



---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>