

# CP1-13R-01



## General Information

|                               |  |
|-------------------------------|--|
| <b>Extended Product Type:</b> | CP1-13R-01   |
| <b>Product ID:</b>            | 1SFA619100R1341  |
| <b>EAN:</b>                   | 7320500381700  |
| <b>Catalog Description:</b>   | CP1-13R-01 Pushbutton  |
| <b>Long Description:</b>      | Compact Pushbutton - Momentary - Flush - Red - Illuminated - Black plastic - 1NC |

## Categories

Products » Low Voltage Products and Systems » Control Products » Pilot Devices » Operator and Pilot Lights

## Ordering

|                                |               |
|--------------------------------|---------------|
| <b>EAN:</b>                    | 7320500381700 |
| <b>Minimum Order Quantity:</b> | 10 piece      |
| <b>Customs Tariff Number:</b>  | 85369001      |

## Dimensions

|                            |          |
|----------------------------|----------|
| <b>Product Net Width:</b>  | 0.030 m  |
| <b>Product Net Height:</b> | 0.030 m  |
| <b>Product Net Depth:</b>  | 0.055 m  |
| <b>Product Net Weight:</b> | 0.018 kg |

## Environmental

|                                 |   |
|---------------------------------|---|
| <b>Ambient Air Temperature:</b> | Operation -25 ... +70 °C  |
| <b>RoHS Status:</b>             | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

## Additional Information

|   |   |
|---|---|
| <b>Actuator Type:</b>                                   | Flush   |
| <b>Additional Information:</b>                          | III. PB   |
| <b>Bezel Material:</b>                                  | Black plastic   |
| <b>Block:</b>   | 1NC   |
| <b>Color:</b>   | Red   |
| <b>Degree of Protection:</b>                            | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 |
| <b>Function:</b>  | Momentary   |
| <b>Illumination:</b>                                    | Illuminated   |
| <b>Lamp Type:</b>                                       | LED 220V AC/DC  |
| <b>Lens Color:</b>                                      | Red   |
| <b>Lower Button Color:</b>                              | Red   |
| <b>Mechanical Durability:</b>                           | 0.5 million   |
| <b>Number of Auxiliary Contacts NC:</b>                 | 1   |
| <b>Order Multiple:</b>                                  | 1 piece   |
| <b>Product Main Type:</b>                               | CP1   |
| <b>Product Name:</b>                                    | Pushbutton  |
| <b>Product Range:</b>                                   | Compact   |
| <b>Product Type:</b>                                    | CP  |
| <b>Rated Frequency (f):</b>                             | 50 / 60 Hz  |
| <b>Rated Operational Current AC-15 (I<sub>e</sub>):</b> | (240V) 1 A<br>(120V) 1.5 A  |
| <b>Rated Operational Current DC-13 (I<sub>e</sub>):</b> | (125V) 0.2 A<br>(24V) 0.3 A                                       |

**Rated Operational Voltage:** 220 V AC/DC

**RoHS Date:** 0626 5

---

### **Certificates and Declarations (Document Number)**

---

**Declaration of Conformity - CE:** 1SFA1-70

**RoHS Information:** 1SFC151012D0202

---

### **Classifications**

---

**E-nummer:** 3717280

**ETIM 4.0:** EC002024 - Accessories for control circuit devices

**ETIM 5.0:** EC002024 - Accessories for control circuit devices

**Object Classification Code:** S

---

