

Ferrule - AI-TWIN 2X16 -16 BU - 3202847

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Ferrule, Sleeve length: 16 mm, Length: 31 mm, Color: blue

The figure shows the version AI-TWIN 2 x 2,5 -10 BU

Why buy this product

- Different versions of the individual TWIN ferrules can be selected for specific applications
- The TWIN ferrules provide a practical way of crimping two conductors in one ferrule
- These special ferrules allow chain bridges to be set up with ease

Key commercial data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	 4 017918 171575
Weight per Piece (excluding packing)	1.62 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Length (b)	31 mm
Maximum stripping length	21 mm
Sleeve length	16 mm
Inner dimension of the insulating collar (d)	8.8 mm
Ferrule diameter	8.5 mm
Insulating collar thickness	0.5 mm
Sleeve wall thickness	0.2 mm

Ambient conditions

Short-term temperature	120 °C
Max. permanent temperature	105 °C

General

Color	blue
-------	------

Ferrule - AI-TWIN 2X16 -16 BU - 3202847

Technical data

General

Components	free from silicone and halogen
Inflammability class according to UL 94	HB
Material	E-CU

Classifications

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201
eCl@ss 8.0	27400201

ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

Approvals

Approvals

Approvals

CSA / CSAus / EAC / cCSAus

Ex Approvals

Approvals submitted

Ferrule - AI-TWIN 2X16 -16 BU - 3202847

Approvals

Approval details

CSA 

CSAus

EAC

cCSAus