

Switching devices with dependent manual operation

SLD 00, 160 A



SLD 00
Fuse-switch-disconnector.

- AC-23B according to IEC 60947-3 at 400 V.
- 4 modules or 50 mm width.
- Fuse NH 00.
- Sealing possibility.



JDDA 00
Earthing device.



KSBD 00
Blocking device.



KN 00
Linking knife



FHHD-A 00
Kit with detachable handle and adapter for fuse-switch-disconnector SLD 00. With this solution the depth is reduced with 35 mm.



FHH
Detachable handle to FHHD-A 000, SLC-FHD 00 and FHD 00.

Note:

Switching devices to be tightened with the torque.
For "Tightening torque" see page 5/6.

Designation	ID No.	Degree of protection	Number of modules	Rated data		Cable connection Al/Cu mm ²	Numbers per kit	Weight kg/each
				M *	400 V			
SLD 00	2CGX0 63050107	IP2X **	4	160 A	160 A	2.5-95 ***	1	1.8

* One module M = 12.5 mm.
** IP1X with open device, depending on design of fuse.
*** Max conductor cross section refers to connection with a stranded or solid conductor.

To be ordered separately:

Designation	ID No.	Number of modules	Rated data	Number per kit	Weight kg/each
JDDA 00	2CGX0 63190376	4	6.1 kA/1 s	1	2.3
KSBD 00	2CGX0 63190109	-	-	3	0.1
KN 00	2CGX0 53190319	-	160 A	3	0.1
FHHD-A 00	2CGX0 53050204	-	-	1	0.03
FHH	2CGX0 43050404	-	-	1	0.02

* One module M = 12.5 mm.