


## KNX Shutter actuator, 4-gang 230 V AC with manual activation



Specification	Order No.	Packing unit	PS	EAN
 DRA plus	2160 00	1	26	4010337101352

### Technical data

Operating voltage:	230 V AC, 50/60 Hz
AC switching voltage:	230 V AC, 50/60 Hz
Loading capacity	6 A/AC1
AC 230 V:	
Connections:	KNX/EIB via connection and branch terminal <b>0595 00</b> load via screw terminals 0.5 to 4 mm <sup>2</sup> single/fine-wire without core jacket 0.5 to 2.5 mm <sup>2</sup> fine-wire with core jacket
Dimensions:	DRA device, 4 depth modules
VDE approval in accordance with:	EN 60669-1, EN 60669-2-1, EN 50428

### Information

- Product family:** Blinds  
**Product type:** Blinds
- Shutter actuator with manual activation and status display for each output. To control electrically operated shutters for a mains voltage of 230 V AC (4 channel).
- The ETS3.0d (or higher) is recommended for configuring and starting up the device. Shutter actuator with integrated bus coupler. Installation on DIN top-hat rail. Connection of various phases.
- Functions:- Independent control of the 4 shutter outputs.
- Shutter position can be directly controlled.
  - Behaviour after bus voltage failure and return can be set.
  - Feedback of position. Active or passive (object can be read out) cyclical feedback functions.
  - Assignments of up to 5 different safety functions (3 wind alarms, 1 rain alarm, 1 frost alarm), or with cyclical monitoring.