

# Temporary single phase outlet and general accessories

## TFU 25, UKRA, AK-ADAS



### TFU 25

Single-phase power outlet for temporary connections, e.g. for a hand lamp or power drill. Mounts directly on the busbar. Conductor cross section, max. 35 mm<sup>2</sup> Al/Cu. Max. fuse 25 A.

Connectors for the PE and N conductors are also needed (see the page about connectors).



### UKRA 90

Universal clamp for fixing cables with Ø 20-90 mm, on mounting rails in a cabinet, for example.



### AK-ADAS

Prefabricated connector for the extension of Al cable, while connecting in a cable distribution cabinet, a service distribution board or in switchgears. Dimensioned in accordance with the cable loading and short-circuit data. Meets the requirements of:  
SEN 24 50 10 Edition 1  
SEN 24 50 12 Edition 1

Flexible XLPE-insulated Cu conductor compressed onto a prefabricated Al/Cu cable connection. The aluminium part is designed for crimping with the Elpress system. The length of all the connectors are 700 mm.

Designation	ID No.	Rated data	Cable connection	Dimensions			Weight
				Height	Width	Depth	
TFU 25	2CGX0 63140001	230 V, 25 A	1.5 -35 Al/Cu	84	30	185	0,3

Designation	ID No.	Diameter Ø	Qty per pack	Weight
		mm		kg/each
UKRA 90	2GLX0 65300013	20-90	1	0.2

Designation	ID Number	Fits aluminium	Conductor cross	Weight
		conductor cross section	section of connector	
		mm <sup>2</sup>	mm <sup>2</sup>	kg/each
AK-ADAS 5025-7	2CGX0 63030075	50	25	0,2
AK-ADAS 7035-7	2CGX0 63030082	70	35	0,2
AK-ADAS 9550-7	2CGX0 63030090	95	50	0,5
AK-ADAS 12070-7	2CGX0 63030097	120	70	0,5
AK-ADAS 15070-7	2CGX0 63030104	150	70	0,6
AK-ADAS 185120-7	2CGX0 63030115	185	120	0,9
AK-ADAS 240120-7	2CGX0 63030118	240	120	1,0