

CC4-01



General Information

Extended Product Type:	CC4-01
Product ID:	1SBN010111R1001
EAN:	3471523130432
Catalog Description:	CC4-01 Lagging Auxiliary Contact Block
Long Description:	CC4-01 Lagging Auxiliary Contact Block

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors Accessories

Ordering

EAN:	3471523130432
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Weight:	0.014 kg
----------------------------	----------

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	100 mm
Package Level 1 Height:	10 mm
Package Level 1 Length:	100 mm
Package Level 1 Gross Weight:	0.01400 kg
Package Level 1 EAN:	3471523130432
Package Level 2 Units:	100 piece
Package Level 3 Units:	2400 piece
Product Packing Type:	Bag

Technical UL/CSA

Tightening Torque UL/CSA:	Auxiliary Circuit 11 in·lb
----------------------------------	----------------------------

Additional Information

Connecting Capacity-Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1...2.5 mm ²
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, q=40°C 16 A
IIT Publishing Status:	Level 0 - Information enabled
Maximum Electrical Switching Frequency:	AC-15 1200 cycles per hour DC-13 900 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Product Main Type:	Accessories for Block Contactors
Product Name:	Auxiliary Contact Block
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V

acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V

Rated Operational Current AC-15 (I_e): (220 / 240V) 4 A
(24 / 127V) 6 A
(400 / 440V) 3 A
(500V) 2 A
(690V) 2 A

Rated Operational Current DC-13 (I_e): (110V) 0.55 A / 60 W
(125V) 0.55 A / 69 W
(220V) 0.27 A / 60 W
(24V) 6 A / 144 W
(250V) 0.27 A / 68 W
(400V) 0.15 A / 60 W
(48V) 2.8 A / 134 W
(500V) 0.13 A / 65 W
(600V) 0.1 A / 60 W
(72V) 1 A / 72 W

Rated Operational Voltage: Auxiliary Circuit 24 ... 690 V

Rated Short-time Withstand Current (I_{cw}): for 0.1s 140 A
for 1.0s 100 A

Terminal Type: Screw Terminals

Wire Stripping Length: Auxiliary Circuit 10 mm

Certificates and Declarations (Document Number)

CB Certificate: CB_SE_70923
CCC Certificate: CCC_2011010304496319
cUL Certificate: UL_20091128-E252354-3-1
Declaration of Conformity - CE: 1SBD250167C2000
EAC Certificate: EAC_RU C-FR ME77 B01048
GOST Certificate: GOST_POCCFR.ME77.B07175.pdf
LR Certificate: LRS_1300087E1
RINA Certificate: RINA_ELE084013XG

Classifications

E-nummer: 3211433
ETIM 4.0: EC002498 - Accessories for low-voltage switch technology
ETIM 5.0: EC002498 - Accessories for low-voltage switch technology
Object Classification Code: K
UNSPSC: 39121500

