

OT400E04P



General Information

| | |
|-------------------------------|--|
| Extended Product Type: | OT400E04P |
| Product ID: | 1SCA022719R1810 |
| EAN: | 6417019230788 |
| Catalog Description: | OT400E04P Switch-disconnector |
| Long Description: | Including a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths. |

Categories

Products » Low Voltage Products and Systems » Switches » Switch Disconnectors

Ordering

| | |
|--------------------------------|---------------|
| EAN: | 6417019230788 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85365080 |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width: | 235 mm |
| Product Net Height: | 185 mm |
| Product Net Depth: | 107 mm |
| Product Net Weight: | 3.7 kg |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 200 mm |
| Package Level 1 Height: | 120 mm |
| Package Level 1 Length: | 310 mm |
| Package Level 1 Gross Weight: | 3.7 kg |
| Package Level 1 EAN: | 6417019230788 |

Environmental

| | |
|---------------------|--|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-06-01 |
|---------------------|--|

Additional Information

| | |
|---|------------------------------------|
| Conventional Free-air Thermal Current (I_{th}): | q=40°C 400 A |
| Conventional Thermal Current (I_{the}): | Fully Enclosed 400 A |
| Dielectric Test Voltage: | 10000 V |
| Earthing Switch Type: | No Additional Type |
| Handle Type: | Pistol |
| IIT Publishing Status: | Level 0 - Information enabled |
| Includes: | Handle and Shaft |
| Mounting Type: | Normal |
| Number of Poles: | 4 |
| Operating Mechanism: | Mechanism at the end of the switch |
| Operating Mode: | Front Operated |

| | |
|---|---|
| Pollution Degree: | 3 |
| Position of Line Terminals: | Top in - bottom out |
| Power Loss: | Per Pole 10 W |
| Product Main Type: | OT |
| Product Name: | Switch-disconnectors |
| Rated Impulse Withstand Voltage (U_{imp}): | 12 kV |
| Rated Insulation Voltage (U_i): | 1000 V |
| Rated Operational Current AC-21A (I_e): | (500V) 400 A (690V) 400 A (380 ... 415V) 400 A |
| Rated Operational Current AC-21B (I_e): | (690V) 400 A (500V) 400 A (380 ... 415V) 400 A |
| Rated Operational Current AC-22A (I_e): | (380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A |
| Rated Operational Current AC-22B (I_e): | (690V) 400 A (500V) 400 A (415V) 400 A |
| Rated Operational Current AC-23A (I_e): | (380 ... 415 V) 400 A (690 V) 400 A (500 V) 400 A |
| Rated Operational Current AC-23B (I_e): | (690V) 400 A (500V) 400 A (380 ... 415V) 400 A |
| Rated Operational Power AC-23A (P_e): | (690V) 400 kW (500V) 280 kW (400 ... 415V) 230 kW (400V) 220 kW (220 ... 240V) 132 kW |
| Rated Short-time Withstand Current (I_{cw}): | for 1.0s 15000 A |
| Special Functions: | No |
| Standards: | IEC |
| Terminal Type: | Lug terminals |
| Terminal Width: | 25 mm |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| BV Certificate: | 1SCC301103D0201 |
| Declaration of Conformity - CE: | 1SCC301136D0202 |
| GL Certificate: | 1SCC301139D0201 |
| LR Certificate: | 1SCC301144D0201 |
| RoHS Information: | 1SCC301149D0202 |

Classifications

| | |
|------------------------------------|--------------------------------|
| E-nummer: | 3171202 |
| ETIM 5.0: | EC000216 - Switch disconnecter |
| Object Classification Code: | Q |

