

# XLBM00-3P-Z



## General Information

<b>Extended Product Type:</b>	XLBM00-3P-Z
<b>Product ID:</b>	1SEP102140R0221
<b>EAN:</b>	7025840021438
<b>Catalog Description:</b>	XLBM00-3P-Z
<b>Long Description:</b>	XLBM00-3P-Z

## Categories

Products » Low Voltage Products and Systems » Fusegear » Fuse Switch Disconnectors » InLine

## Ordering

<b>EAN:</b>	7025840021438
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85363009

## Dimensions

<b>Product Net Width:</b>	5 cm
<b>Product Net Height:</b>	66 cm
<b>Product Net Depth:</b>	18.1 cm
<b>Product Net Weight:</b>	2.5 kg

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Gross Weight:</b>	2.5 kg
<b>Product Packing Type:</b>	Shrink-Wrap

## Environmental

<b>RoHS Status:</b>	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
---------------------	--

## Additional Information

<b>Connecting Capacity:</b>	Busbar Z-bar
<b>Degree of Protection:</b>	acc. to IEC 60529 IP30
<b>Frequency (f):</b>	50/60 Hz
<b>Fuse Protected Short-Circuit Making:</b>	50 kiloampere rms
<b>Fuse Protected Short-Circuit Withstand:</b>	50 kiloampere rms
<b>Fuse Size:</b>	NH00
<b>Handle Type:</b>	3P
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Mounting Type:</b>	185mm Z-Busbar/support mounting facilities
<b>Product Main Type:</b>	InLine
<b>Product Name:</b>	Fuse Switch Disconnecter
<b>Rated Current (I<sub>n</sub>):</b>	160 A
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	8 kV
<b>Rated Operational Current AC-21B (I<sub>e</sub>):</b>	(690V) 160 A
<b>Rated Operational Current AC-22B</b>	(500V) 160 A

**(I<sub>e</sub>):****Rated Operational Current AC-23B** (380 ... 415V) 125 A**(I<sub>e</sub>):****Terminal Connection Type:** Bottom**Terminal Type:** Bolt

---

**Certificates and Declarations (Document Number)**

---

**Declaration of Conformity - CE:** 1SEP500034P0001

---

**Classifications**

---

**ETIM 4.0:** EC001040 - Fuse switch disconnecter**ETIM 5.0:** EC001040 - Fuse switch disconnecter**Object Classification Code:** Q

---

