

Tubo

Gf design




- Unique Scandinavian design
- Deep recessed COB
- Quick connection

Further information can be found on our homepage: www.tlg.no, where you can also download a brochure from GF Design.



LED-Chip: Cree CXB1407
 Driver: Dimmable driver
 Beam angle: 24°
 Material: Aluminium
 Color: White or Black
 Color tolerance: MacAdam 3
 Expected lifetime: (L70B50) 50 000 Hours.



Art.no.	Color	Power	Lumen out	CCT	CFI	Cut-out hole	Dimensions (ØxH)
32 345 12	○ White	9W	500 lm	2700K	>90	62 mm	70x103 mm
32 345 13	○ White	9W	550 lm	3000K	>90	62 mm	70x103 mm
32 345 15	● Black	9W	350 lm	2700K	>90	62 mm	70x103 mm
32 345 16	● Black	9W	400 lm	3000K	>90	62 mm	70x103 mm
S56001	⏏ SLC Trailing edge dimmer						(see page 51)
S23023	⏏ DALI/Trailing edge dimmer						(see page 53)

Owi

Gf design



- Unique Scandinavian design
- Quick connection

Further information can be found on our homepage: www.tlg.no, where you can also download a brochure from GF Design.



LED-Chip: Cree CXB1407
 Driver: Dimmable driver
 Beam angle: 24°
 Material: Aluminium
 Color: White or Black
 Color tolerance: MacAdam 3
 Expected lifetime: (L70B50) 50 000 Hours.



Art.no.	Color	Power	Lumen out	CCT	CFI	Cut-out hole	Dimensions (ØxH)
32 345 00	○ White	9W	650 lm	2700K	>90	62 mm	70x56 mm
32 345 01	○ White	9W	700 lm	3000K	>90	62 mm	70x56 mm
32 345 03	● Black	9W	600 lm	2700K	>90	62 mm	70x56 mm
32 345 04	● Black	9W	650 lm	3000K	>90	62 mm	70x56 mm
S56001	⏏ SLC Trailing edge dimmer						(see page 51)
S23023	⏏ DALI/Trailing edge dimmer						(see page 53)

› For other versions, more product info or ordering, contact us at: www.tlg.no