

Insertion bridge - EB 3-25/PT - 3260160

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Insertion bridge, pitch: 25 mm, length: 73 mm, width: 47.8 mm, number of positions: 3, color: red



Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 046356 779128
GTIN	4046356779128
Weight per Piece (excluding packing)	78.500 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Technical data

Color	red
Material	Metal
Number of positions	3
Pitch	25 mm
Length	73 mm
Height	28.6 mm
Width	47.8 mm
Flammability rating according to UL 94	V0
Maximum load current	150 A

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
------------	---

Insertion bridge - EB 3-25/PT - 3260160

Technical data

Environmental Product Compliance

	No hazardous substances above threshold values
--	--

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

ETIM

ETIM 3.0	EC000886
ETIM 4.0	EC000902
ETIM 5.0	EC000489
ETIM 6.0	EC000489
ETIM 7.0	EC000489

UNSPSC

UNSPSC 6.01	30211827
UNSPSC 7.0901	39121424
UNSPSC 11	39121424
UNSPSC 12.01	39121424
UNSPSC 13.2	39121426

Approvals

Approvals

Approvals


EAC / EAC


Ex Approvals

Approval details

Insertion bridge - EB 3-25/PT - 3260160

Approvals

EAC		EAC-Zulassung
-----	---	---------------

EAC		RU C- DE.A*30.B.01742
-----	---	--------------------------