467126EX

TAIS-EX INTERLOCKED SOCKET W/O PROTECTION 2P+E 16A 230V 50-60HZ IP66 FOR ATEX ZONES 2D 3G

Registry	
Net weight	2,8
Min order quantity	1
EAN Code	8014950051793

Reference Standards	Directive
EN 60079-0/A11: 2013	2014/34/EU
EN 60079-0: 2012	2014/35/EU
EN 60079-15: 2010	
EN 60079-31: 2014	
EN 60309-1/A1: 2007	
EN 60309-1/A1EC: 2014	
EN 60309-1/A2: 2012	
EN 60309-1: 1999	
EN 60309-2/A1: 2007	
EN 60309-2/A2: 2012	
EN 60309-2: 1999	
EN 60309-4/A1: 2012	
EN 60309-4: 2007	

Marks
CE

Technical data	
Dimensions	125X380X160 mm
Hole type	M25
Frequency	50-60Hz
Protection level	IP66
Poles	2P+⏚
Clock Position	6
Nominal Operating Voltage	230V
Manufacturing Material	Thermosetting
Width	125 mm
Nominal current	16A
Execution	WALL MOUNTING
Protection	NONE
Insulation Class	II

Atex	
ATEX application zone	Zona/Zone 2, 21 and 22
Notified body (CE)	CE 0051
Certificate Number IECEx	IECEx EXA 15.0004X
Atex Dust Nominal Current	16
Atex Gas Nominal Current	16
Atex Dust Marking	Ex tb IIIC T80°C Db
Atex Gas Marking	Ex nR IIC T6 Gc
Certificate Number ATEX	TÜV IT 13 ATEX 049 X
GAS Dissipable Power	-
DUST Dissipable Power	-
Min. Amb. Temp.	-20°C
Max. Amb. Temp.	+40°C
Group & Cat. ATEX GAS	II 3G
Group & Cat. ATEX DUST	II 2D

Attachments
DXF drawing