

CR-P110AC2



General Information

| | |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type: | CR-P110AC2 |
| Product ID: | 1SVR405601R7000 |
| EAN: | 4013614498299 |
| Catalog Description: | CR-P110AC2 Pluggable interface relay |
| Long Description: | The CR-P110AC2 pluggable interface relay is from the CR-P (pcb) relay range. This relay operates with a 110 V AC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 8 A. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories. |

Categories

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Interface Relays and Optocouplers

Ordering

| | |
|--------------------------------|---------------|
| EAN: | 4013614498299 |
| Minimum Order Quantity: | 10 piece |
| Customs Tariff Number: | 85364900 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width: | 12.7 mm |
| Product Net Height: | 15.7 mm |
| Product Net Depth: | 29.0 mm |
| Product Net Weight: | 0.014 kg |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 10 piece |
| Package Level 1 Width: | 332.0 mm |
| Package Level 1 Height: | 28.0 mm |
| Package Level 1 Length: | 17.0 mm |
| Package Level 1 Gross Weight: | 0.157 kg |
| Package Level 1 EAN: | 4013614373039 |

Technical

| | |
|------------------------------------------------------|------------------------------------|
| Function: | Pluggable pcb interface relay CR-P |
| Sub-Function: | Relay w/o built in LED |
| Output: | 2 c/o (SPDT) contacts |
| Output Signal: | 250 V / 8 A |
| Rated Control Supply Voltage (U_s): | 110 V AC |

Environmental

| | |
|---------------------|-----------------------------------------------------------------|
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|---------------------|-----------------------------------------------------------------|

Certificates and Declarations (Document Number)

| | |
|----------------------------------------|----------------------|
| CCC Certificate: | CCC_2007010303228779 |
| CSA Certificate: | CSA_1587291 |
| cUR Certificate: | cUR_E244330 |
| Declaration of Conformity - CE: | 1SAD938500-0159 |

| | |
|--------------------------|--------------------------|
| EAC Certificate: | EAC_RU_C-PL.ME77.B.01873 |
| GOST Certificate: | GOST_POCC_DE.AB76.D02256 |
| RMRS Certificate: | RMRS_12.04008.250 |
| RoHS Information: | 1SAA981040-4403 |
| UR Certificate: | UR_E244330 |
| VDE Certificate: | VDE_40019129 |

Classifications

| | |
|------------------------------------|----------------------------|
| Object Classification Code: | K |
| ETIM 4.0: | EC001437 - Switching relay |
| ETIM 5.0: | EC001437 - Switching relay |
| UNSPSC: | 39121500 |

