

PRODUCT-DETAILS

MPR63PRO

Modular Combi Plastic, One 16A (346-415V) outlet (3P+N+E), One 32A (346-415V) outlet (3P+N+E), One 63A (346-415V) outlet (Not with RCD, 3P+N+E) and three schuko outlets (1P+E) 10/16A (250 V). 3xMCB S201 C16 and S203 C16, S203 C32, S203 C63, RCD F204 A-40/0,03



General Information

Extended Product Type	MPR63PRO
Product ID	2CMA101808R1000
EAN	7392696018081
Catalog Description	Modular Combi Plastic, One 16A (346-415V) outlet (3P+N+E), One 32A (346-415V) outlet (3P+N+E), One 63A (346-415V) outlet (Not with RCD, 3P+N+E) and three schuko outlets (1P+E) 10/16A (250 V). 3xMCB S201 C16 and S203 C16, S203 C32, S203 C63, RCD F204 A-40/0,03
Long Description	Modular Combi Plastic, One 16A (346-415V) outlet (3P+N+E), One 32A (346-415V) outlet (3P+N+E), One 63A (346-415V) outlet (Not with RCD, 3P+N+E) and three schuko outlets (1P+E) 10/16A (250 V). 3xMCB S201 C16 and S203 C16, S203 C32, S203 C63, RCD F204 A-40/0,03

Ordering

E-Number (Sweden)	E2466477
EAN	7392696018081
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	250 mm
-------------------	--------

Product Net Height	750 mm
Product Net Length	250 mm
Product Net Depth / Length	165 mm
Product Net Weight	5.4 kg

Container Information

Package Level 1 Width	2 mm
Package Level 1 Depth / Length	252 mm
Package Level 1 Height	752 mm
Package Level 1 Gross Weight	5.4 kg
Package Level 1 EAN	7392696018081
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0004
Declaration	2CMC700005D0004
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0004

Additional Information

Additional Information	3P+N+E, Incoming terminal 35 mm2
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 mm ²
Cable Entry Position	Cable entry,4 knock-outs at the top,suitable for 2xØ40mm and 2xØ25mm,at the bottom 2xØ40,5mm, 1xØ47,5mm
Cable Length	0 m
Color	Grey
Connection Type	Screw Clamp
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Modular combi
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#MPR63PRO
Mounting Holes	84x80
Mounting Type	Vertical
Number of Poles	5
Number of RCDs 30mA	1
Number of RCDs	1
Order Multiple	1 piece
Product Main Type	MPR

Product Name	Modular Combi
Rated Current (I_n)	63 A
Rated Residual Current	30 mA
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 61439-1 IEC 61439-2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000026M0001
Installation Manual	2CMC000026M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440501
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Modular Combination Boxes

