

OT125FT3



General Information

Extended Product Type:	OT125FT3
Product ID:	1SCA105060R1001
EAN:	6417019391908
Catalog Description:	OT125FT3 Switch-disconnector
Long Description:	Front operated switch-disconnector. Types OT 16...125 include protected terminal clamps, IP 20.

Categories

Products » Low Voltage Products and Systems » Switches » Switch Disconnectors

Ordering

EAN:	6417019391908
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	70 mm
Product Net Height:	100 mm
Product Net Depth:	67 mm
Product Net Weight:	0.4 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	81 mm
Package Level 1 Height:	79 mm
Package Level 1 Length:	112 mm
Package Level 1 Gross Weight:	0.4 kg
Package Level 1 EAN:	6417019391908

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q3
---------------------	---

Additional Information

Cable Cross-Section:	10...70 mm ²
Conventional Free-air Thermal Current (I_{th}):	q=40°C 125 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 125 A
Earthing Switch Type:	No Additional Type
Handle Type:	None
IIT Publishing Status:	Level 0 - Information enabled
Includes:	None
Mounting Type:	Door Mounting
Number of Poles:	3
Operating Mechanism:	Mechanism on top of the switch
Operating Mode:	Front Operated
Order Multiple:	10 piece
Pollution Degree:	3

Position of Line Terminals:	Top in - bottom out
Power Loss:	Per Pole 0.36 W
Product Main Type:	OT
Product Name:	Switch-disconnectors
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	750 V
Rated Operational Current AC-21A (I_e):	(500V) 125 A (690V) 125 A (380 ... 415V) 125 A
Rated Operational Current AC-22A (I_e):	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A (I_e):	(500 V) 70 A (380 ... 415 V) 90 A (690 V) 50 A
Rated Operational Power AC-23A (P_e):	(220 ... 240V) 22 kW (400V) 45 kW (415V) 45 kW (500V) 45 kW (690V) 45 kW
Rated Operational Voltage:	750 V
Rated Short-time Withstand Current (I_{cw}):	for 1.0s 2.5 kiloampere rms
Special Functions:	No
Standards:	IEC
Terminal Type:	Screw Terminals

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SCC301168D0201
RoHS Information:	1SCC301183D0201

Classifications

E-nummer:	3170950
ETIM 5.0:	EC000216 - Switch disconnecter
Object Classification Code:	Q

