




## 261432EX

**ATEX START - STOP PUSH-BUTTON PANEL IN WATERTIGHT WALL-MOUNTING  
ENCLOSURE 10A 380V 1XM20 62X80X51 IP66**

Registry		Technical data	
Net weight	0,255	Dimensions	62X108 mm
Min order quantity	1	Hole type	M20
EAN Code	8014950058389	Number of entries in enclosure	1
Reference Standards	Directive	Rated current/voltage	10A 400V~
EN 60079-0/A11: 2013	2014/30/EU	Frequency	50/60Hz
EN 60079-0: 2012	2014/34/EU	Protection level	IP66
EN 60079-15: 2010	2014/35/EU	Poles	1P
EN 60079-31: 2014		Nominal Operating Voltage	400V
EN 60669-1/A1: 2002		Manufacturing Material	Thermosetting
EN 60669-1/A2: 2008		DEVICE FUNCTION	Other functions
EN 60669-1/S1: 2009		Width	62 mm
EN 60669-1: 1999		Nominal current	10A
EN 60947-5-1/A1: 2009		Execution	WALL MOUNTING
EN 60947-5-1: 2004		Modules Number	Z_BLANK
		Insulation Class	II
Marks		Atex	
		ATEX application zone	Zona/Zone 2 and 22
		Atex Dust Nominal Current	-
		Atex Gas Nominal Current	-
		Atex Dust Marking	Ex tc IIIC T70°C Dc
		Atex Gas Marking	Ex nR IIC T6 Gc
		GAS Dissipable Power	-
		DUST Dissipable Power	-
		Min. Amb. Temp.	-20°C
		Max. Amb. Temp.	+40°C
		Group & Cat. ATEX GAS	II 3G
		Group & Cat. ATEX DUST	II 3D
Attachments			
		DXF drawing	