



477427EX

CEE-EX MOBILE PLUG 3P+N+E 63A 400V 50/60HZ 6H IP66

Registry		Technical data	
Net weight	0,905	Hole type	Pg29
Min order quantity	1	Frequency	50-60Hz
EAN Code	8014950009688	Protection level	IP66
Reference Standards	Directive	Poles	3P+N+⏏
EN 60079-0/A11: 2013	2014/34/EU	Clock Position	6
EN 60079-0: 2012	2014/35/EU	Standard plug-socket	EN60309-2
EN 60079-15: 2010		Nominal Operating Voltage	400V
EN 60079-31: 2014		Insulating Voltage	500V
EN 60309-1/A1: 2007		Manufacturing Material	Thermoplastic
EN 60309-1/A1EC: 2014		Nominal current	63A
EN 60309-1/A2: 2012		Execution	MOBILE
EN 60309-1: 1999		Shape	Straight
EN 60309-2/A1: 2007		Atex	
EN 60309-2/A2: 2012		ATEX application zone	Zona/Zone 2 and 22
EN 60309-2: 1999		Atex Dust Marking	Ex tc IIIC T65°C Dc
		Atex Gas Marking	Ex nA IIC T6 Gc
		Group & Cat. ATEX GAS	II 3G
		Group & Cat. ATEX DUST	II 3D
Marks		Attachments	
CE		DXF drawing	