



SLC SQUARY R62 WH 650TED 927

IP54 36°

The Squary downlight is available in white or black. It's small but has a strong impression. The sharp minimalistic edge gives the downlight character and at the same time reduces glare. Squary gives the room a warm and quiet atmosphere.



Light technic	
Product ID	3234506
Beam angle	36 °, Medium beam 21-40° °
Lamp efficacy	72 lm/W
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700 - 2700 K
Rated luminous flux according to IEC 62722-2-1	650 lm
Colour of light	White
Luminous flux	650 - 650 lm
Rated life time L70/B50 at 25 °C	50000 Hours
Rated life time L90/B10 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	72.2 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	II
Colour housing	White
Surface protection	Powder coating
Suitable for lamp power	9 - 9
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Covering of the luminaire with thermally insulating material possible	No

23.03.2021

Subject to changes and printing errors

Control gear included	Yes
Fit for workplace according to EN 12464-1	No
Max. system power	9 W
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-10 - 45 °C
Dimming phase cut-off	Yes
Power factor	0.95
Dimming method	Trailing edge
Input	
Voltage type	AC/DC
Nominal voltage	220 - 240 V
Output	
LED nominal current at constant current	230 - 230 mA
Installation	
Height/depth	53 mm
Built-in width	62 mm
Built-in height/depth	43 mm
Length	70 mm
Built-in length	62 mm
Width	70 mm
Outer diameter	70 mm
Conductor cross section	0.35 mm ²
Connection type	Plug clamp
Built-in diameter	62 mm
Suitable for suspended mounting	No
Number of poles	3
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
GTIN	7070938054386
Pallet length	1200 mm
M-pack length	635 mm
F-pack length	110 mm

23.03.2021
Subject to changes and printing errors

23.03.2021

Subject to changes and printing errors