



30483515

Double change-over switch insert with rocker 2gang surface-mounted/flush-mounted, isolated input terminals Berker W.1

Technical features

Architecture

| | |
|----------------------|--------------------------|
| Type of control unit | double rocker |
| Technical version | isolated input terminals |

Configuration

- Change-over contact/change-over switch

Controls and indicators

- No

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |

Electric current

| | |
|-------------------|-------|
| Switching current | 10 AX |
|-------------------|-------|

Materials

| | |
|-----------------------|----------------------|
| Colour of design line | grey |
| Colour | dark grey |
| RAL colour | RAL 7011 - Iron grey |
| Material | thermoplastic |
| Surface appearance | mat |

Dimensions

| | |
|--------|-------|
| Depth | 42 mm |
| Height | 70 mm |
| Width | 70 mm |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | for screw fastening |
|-------------------|---------------------|

Connection

| | |
|--------------------|--------------|
| Type of connection | Quickconnect |
|--------------------|--------------|

- with plug-in terminals

Equipment

- without lighting (cannot be illuminated)

Safety

| | |
|---------------------|------|
| Protection index IP | IP55 |
|---------------------|------|

Use conditions

| | |
|-------------------------------|-------------|
| Operating temperature | -40...30 °C |
| Storage/transport temperature | -50...50 °C |

Identification

| | |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line | Berker W.1 |

Instructions

| | |
|------------------|--|
| Information text | Pins of quick-release lock made of ZAMAK |
|------------------|--|

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-