




30863515



Control change-over switch insert, rocker surface-mounted/flush-mounted with lens, Berker W.1, grey matt

Technical features

Architecture

Type of control unit single rocker

Configuration

- Change-over

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Electric current

Switching current 10 AX

Materials

Colour of design line grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material thermoplastic

Surface appearance matt

Dimensions

Depth 42 mm

Height 70 mm

Width 70 mm

Installation, mounting

Installation mode for screw fastening

Connection

Type of connection Quickconnect

- with plug-in terminals

- with N-terminal

Cable

- with cable entry at top and bottom

Equipment

- with **230 V LED unit**

- for monitoring circuit

Use

Differentiation characteristic 2 - Sales with lens

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Main design line	Berker W.1
------------------	------------

Instructions

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
