



30723505



IP55

On/off switch 2pole with imprint "0" and "I" surface-mounted Berker W.1, grey/light grey matt

Technical features

Architecture

Type of control unit single rocker

Configuration

- ample room for wiring under the bases of the inserts
- 2 x 1- pole Off

Connectivity

- with mechanical encoding of rocker mount, that allows only one correct positioning of the rocker on the insert

Main electrical features

Nominal voltage 250 V
Rated voltage 250 V AC

Electric current

Switching current 10 AX

Materials

Colour of design line grey/light grey
Colour dark grey
RAL colour RAL 7011 - Iron grey
Material thermoplastic
Surface appearance matt

Dimensions

Depth 61,5 mm
Height 76 mm
Width 76 mm

Installation, mounting

Installation mode for screw fastening

Connection

Type of connection Quickconnect

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with N-terminal
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Pins of quick-release lock made of ZAMAK
------------------	--
