



3036



## Change-over switch Light control

Technical features

### Architecture

Type of control unit single rocker

### Functions

Switching angle 3,5 °

### Configuration

- Off/change-over

### Controls and indicators

- No

### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

### Electric current

Switching current 10 AX (100 W Self Ballasted Lamp (SBL))

### Materials

Material Plastic/metal

Surface appearance matt

### Dimensions

Depth 42 mm

Insertion depth 31 mm

Height 71 mm

Width 71 mm

### Installation, mounting

Installation mode with spreader claws, for screw fastening

### Connection

Connection terminals according to IEC 60669-1

Connection terminals according to VDE 0632-1

Type of connection Quickconnect

- with plug-in terminals

### Equipment

- for lighting and monitoring circuit

### Safety

Protection index IP IP20

---

**Identification**

---

|                       |                             |
|-----------------------|-----------------------------|
| Application, usage    | HVAC control, Light control |
| Appliance switch type | No                          |
| Main design line      | Light control               |

---

**Instructions**

---

|                  |  |
|------------------|--|
| Information text | spreader claws, insulated to the supporting ring, self-resetting |
|------------------|--|

---

- A control change-over switch is shown here as an example. With 2-pole and 3-pole control on/off switches, other rocker switches and neon lamp units are required.
-