



5031



Push-button, NO contact Light control

Technical features

Architecture

Type of control unit	rocker
----------------------	--------

Functions

Switching angle	3,5 °
-----------------	-------

Configuration

- Normally open contact	
-------------------------	--

Main electrical features

Nominal voltage	250 V
-----------------	-------

Rated voltage	250 V AC
---------------	----------

Electric current

Momentary-contact current	10 A
---------------------------	------

Materials

Material	Plastic/metal
----------	---------------

Dimensions

Depth	41,6 mm
-------	---------

Insertion depth	30 mm
-----------------	-------

Contact spacing	> 3 mm
-----------------	--------

Height	71 mm
--------	-------

Width	71 mm
-------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Conductor cross-section (rigid)	max. 2,5 mm ²
---------------------------------	--------------------------

Connection terminals	according to IEC 60669-1
----------------------	--------------------------

Connection terminals	according to VDE 0632-1
----------------------	-------------------------

- with plug-in terminals	
--------------------------	--

Equipment

- for lighting and monitoring circuit	
---------------------------------------	--

Safety

Protection index IP	IP20
---------------------	------

Identification

Application, usage	Light control
--------------------	---------------

Main design line	Light control
------------------	---------------

Instructions

Information text

spreader claws, insulated to the supporting ring, self-
resetting