



50453522



IP55

Push-button, NO contact surface-mounted Berker W.1, polar white matt

Technical features

Architecture

Type of control unit	single rocker
----------------------	---------------

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
-----------------	-------

Rated voltage	250 V AC
---------------	----------

Electric current

Momentary-contact current	10 A
---------------------------	------

Materials

Colour of design line	polar white
-----------------------	-------------

Colour	polarwhite
--------	------------

Colour	white
--------	-------

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Material	Plastic/metal
----------	---------------

Surface appearance	matt
--------------------	------

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
-----------------------	-------------

Storage/transport temperature	-50...50 °C
-------------------------------	-------------

Identification

Main design line	Berker W.1
------------------	------------

Instructions

Information text	Pins of quick-release lock made of ZAMAK

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
