



50453525



IP55

Push-button, NO contact surface-mounted Berker W.1

Technical features

Architecture

Type of control unit	single rocker
----------------------	---------------

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Momentary-contact current	10 A
---------------------------	------

Materials

Colour of design line	grey
Colour	light grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	Plastic/metal
Surface appearance	matt

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Main design line	Berker W.1
------------------	------------

Instructions

Information text	Pins of quick-release lock made of ZAMAK

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
