



50463522



**Push-button insert, change-over contact, illuminated surface-mounted/flush-mounted with lens, Berker W.1, polar white matt**

Technical features

#### Architecture

Type of control unit rocker

#### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

#### Electric current

Momentary-contact current 10 A

#### Materials

Colour of design line polar white

Colour polarwhite

Colour white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Surface appearance matt

#### Dimensions

Depth 42 mm

Height 71 mm

Width 71 mm

#### Installation, mounting

Installation mode for screw fastening

#### Connection

- with plug-in terminals
- with N-terminal

#### Equipment

- with (blue) 230 V LED unit
- for lighting and monitoring circuit

#### Use

Differentiation characteristic 2 - Sales with lens

#### Safety

Protection index IP IP55

#### Use conditions

Operating temperature -40...30 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	------------------------------------------

---

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.

---