



50763505

IP55

Push-button change-over contact, illuminated surface-mounted with lens, Berker W.1, grey/light grey matt

Technical features

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Rated voltage	250 V AC
---------------	----------

Electric current

Momentary-contact current	10 A
---------------------------	------

Materials

Colour of design line	grey/light grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	61,5 mm
Height	76 mm
Width	76 mm

Connection

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals
- with N-terminal

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with {\\b blue} 230 V LED unit
- for lighting and monitoring circuit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 2 - Sales	with lens
--	-----------

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
-----------------------	-------------

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Pins of quick-release lock made of ZAMAK
------------------	--