



6130773515



## Intermediate switch insert with rocker surface-mounted/flush-mounted Berker W.1, grey matt

### Technical features

#### Architecture

Type of control unit	single rocker
----------------------	---------------

#### Configuration

- intermediate
----------------

#### Main electrical features

Nominal voltage	250 V
-----------------	-------

Rated voltage	250 V AC
---------------	----------

#### Electric current

Switching current	10 AX
-------------------	-------

#### Materials

Colour of design line	grey
-----------------------	------

Colour	dark grey
--------	-----------

RAL colour	RAL 7011 - Iron grey
------------	----------------------

Material	thermoplastic
----------	---------------

Surface appearance	matt
--------------------	------

#### Dimensions

Depth	42 mm
-------	-------

Height	70 mm
--------	-------

Width	70 mm
-------	-------

#### Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

#### Connection

Type of connection	Quickconnect
--------------------	--------------

- with plug-in terminals
--------------------------

#### Safety

Protection index IP	IP55
---------------------	------

#### Use conditions

Operating temperature	-40...30 °C
-----------------------	-------------

Storage/transport temperature	-50...50 °C
-------------------------------	-------------

#### Identification

Application, usage	Surface-mounted wet-room installation
--------------------	---------------------------------------

Main design line	Berker W.1
------------------	------------

### Instructions

---

Information text

Pins of quick-release lock made of ZAMAK

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-