

Cable-mate cableboxes for dry areas

**AK2-SU enclosure base IP40**

- For wall mounting (not suitable for attachment to wiring-duct mounting plate).
- Each cable box includes 3 slide-in KBS 16 mm and 1 slide-in blind cover.
- Matching AK2 front part can be ordered separately.

Order number:	AT2258
EAN:	8712259264745
Mounting method	Universal
Shape	Rectangular
Equipped with	Other
Length	120 mm
Width	95 mm
For tube diameter	16 mm
Inlet from the rear	No
Number of inlets	10
Material	Plastic
Halogen free	Yes
Surface protection	Untreated
Colour	Grey
Degree of protection (IP)	IP40
Cover model	None
Transparent cover	No
Cover attachment	Snapped on
Sealable	No
Circuit integrity	None
With screening	No
Max. conductor cross section	6 mm ²
Depth	40 mm
Mounting in the soil	No
Mounting under water	No
Tackable	No
Type of housing feed-through	Preembossing
Castable	No
With casting compound	No
Rated insulation voltage U _i	690 V
Weatherproof	No
Operating temperature	-40 - 70 °C
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Dispatch	15

Cable-mate® is the innovative, prize-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.