

Cable-mate junction boxes for a watertight installation

AK2 Enclosure base



- Metric input M20.
- For early mounting on cable tray mounting plates.
- Quick fastening screw included.
- Bottom with mounting bosses for fastening DIN rails, among other things.
- Matching AK2 front part can be ordered separately.

Order number:	AT2292
EAN:	8712259057477
Halogen free	Yes
Amount Packaging	5 x 10 st.
Mounting method	Universal
Shape	Rectangular
Equipped with	Other
Length	120 mm
Width	95 mm
For tube diameter	16/19 mm
Inlet from the rear	No
Number of inlets	8
Material	Plastic
Surface protection	Untreated
Colour	Grey
Degree of protection (IP)	IP65
Cover model	None
Transparent cover	No
Cover attachment	Snapped on
Sealable	No
Circuit integrity	None
With screening	No
Max. conductor cross section	6 mm ²
Depth	45 mm
Mounting in the soil	No
Mounting under water	No
Tackable	No
Type of housing feed-through	Thread and prestamping
Castable	Yes
With casting compound	No
Rated insulation voltage Ui	690 V
Weatherproof	No
Operating temperature	-40 - 70 °C
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Dispatch	50

Cable-mate® is the innovative, prize-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.