

PRODUCT-DETAILS

# ADU 95

## ADU 95 Uninsulated connector



### General Information

Extended Product Type	ADU 95
Product ID	2CGD000498A1000
EAN	7331980000647
Catalog Description	ADU 95 Uninsulated connector
Long Description	Uninsulated connector suitable for connection to ABB Kabeldon IP 00 PE/PEN busbars. Connectable conductor area 1,5-95 mm <sup>2</sup> .

### Popular Downloads

Data Sheet, Technical Information	2CGC0036
Instructions and Manuals	2CGD000666S1000

### Dimensions

Product Net Width	21 mm
Product Net Height	51 mm
Product Net Depth / Length	63 mm
Product Net Weight	0.88 kg

---

## Technical

---

Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Operational Voltage	690 V
Standards	IEC 61238-1-1
Cable Cross-Section	1.5...95 mm <sup>2</sup>
Degree of Protection	acc. to IEC 60529 IP00
Tightening Torque	20 N·m Wire-Clamp 10..20 N·m

---



---

## Certificates and Declarations (Document Number)

---

Declaration	2CGC0049
Instructions and Manuals	2CGD000666S1000
RoHS Information	2CGC0040

---



---

## Container Information

---

Package Level 1 Units	bag 1 piece
Package Level 1 Width	21 mm
Package Level 1 Depth / Length	63 mm
Package Level 1 Height	51 mm
Package Level 1 Gross Weight	0.088 kg
Package Level 2 Units	box 50 piece
Package Level 2 Width	244 mm
Package Level 2 Depth / Length	194 mm
Package Level 2 Height	215 mm
Package Level 2 Gross Weight	4.4 kg

---



---

## Classifications

---

ETIM 6	EC000001 - Busbar terminal
ETIM 7	EC000001 - Busbar terminal
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Sweden)	0732797

---

---

## Categories

---

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

