

■ DESCRIPCIÓN / DESCRIPTION


Empotrable orientable (45°) de base circular y realizado en zamak. Para lámpara de Ø50mm, tanto de 12V, 230V o LED.

Adjustable (45°) recessed spot, zamak made. Available for 12V, 230V and LED:

Einbaustrahler runde Basis druck-Guss. Erhaeltlich für Kaltlichtspiegellampen in 12V, 230V und LED.

Encastré orientable (45°) rond, en zamak, pour lampes halogènes de 12V et 230V, et LED.

■ ref. 120



■ CARACTERÍSTICAS / FEATURES

CE IP23 EXT. 850°C

ref. 120 - LED*

230V LED 30°

BRIDGELUX 9'4 W 9'5 W

Color Temperature: Neutral white (4100K) Warm white (3000K)
 CRI: 80 82
 Current: 1000 mA 1000 mA
 Luminous flux: (Tc=25°C) 700 lm (Tc=25°C) 630 lm
 (Tc=65°C) 630 lm (Tc=65°C) 570 lm
 Angle: 30° 30°
 lm Depreciation: 70% after 50.000 hours

Incluye lámpara y equipo / Include lamp and driver.
 * Disponibles diferentes versiones de LED. Consultar.
 * Available different types of LED, please ask.

ref. 120 - G 5.3

12V MAX. 50W GU 5.3 QR-CBC 51

ref. 120 - GU/GZ 10

230V MAX. 50W GU/GZ 10 PAR 16

120 300° 45°

Blanco White	Cromo Chrome	Oro Gold 24k
Aluminio Aluminium	Niquel Rayado Natural Nikel Brushed	

Consultar acabados especiales Request special finishes

■ DATOS FOTOMÉTRICOS / PHOTOMETRIC DATA

