

# CR-P230AC2



## General Information

|                               |  |
|-------------------------------|--|
| <b>Extended Product Type:</b> | CR-P230AC2   |
| <b>Product ID:</b>            | 1SVR405601R3000  |
| <b>EAN:</b>                   | 4013614498251  |
| <b>Catalog Description:</b>   | CR-P230AC2 Pluggable interface relay   |
| <b>Long Description:</b>      | The CR-P230AC2 pluggable interface relay is from the CR-P (pcb) relay range. This relay operates with a 230 V AC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 8 A. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories. |

## Categories

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Interface Relays and Optocouplers

## Ordering

|                                |               |
|--------------------------------|---------------|
| <b>EAN:</b>                    | 4013614498251 |
| <b>Minimum Order Quantity:</b> | 10 piece      |
| <b>Customs Tariff Number:</b>  | 85364900      |

## Dimensions

|                            |          |
|----------------------------|----------|
| <b>Product Net Width:</b>  | 12.7 mm  |
| <b>Product Net Height:</b> | 15.7 mm  |
| <b>Product Net Depth:</b>  | 29.0 mm  |
| <b>Product Net Weight:</b> | 0.014 kg |

## Container Information

|                                      |               |
|--------------------------------------|---------------|
| <b>Package Level 1 Units:</b>        | 10 piece      |
| <b>Package Level 1 Width:</b>        | 332.0 mm      |
| <b>Package Level 1 Height:</b>       | 28.0 mm       |
| <b>Package Level 1 Length:</b>       | 17.0 mm       |
| <b>Package Level 1 Gross Weight:</b> | 0.157 kg      |
| <b>Package Level 1 EAN:</b>          | 4013614373060 |

## Technical

|  |                                    |
|--|------------------------------------|
| <b>Function:</b>                                     | Pluggable pcb interface relay CR-P |
| <b>Sub-Function:</b>                                 | Relay w/o built in LED             |
| <b>Output:</b>                                       | 2 c/o (SPDT) contacts              |
| <b>Output Signal:</b>                                | 250 V / 8 A                        |
| <b>Rated Control Supply Voltage (U<sub>s</sub>):</b> | 230 V AC                           |

## Environmental

|                     |   |
|---------------------|---|
| <b>RoHS Status:</b> | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|---------------------|---|

## Certificates and Declarations (Document Number)

|  |                      |
|--|----------------------|
| <b>CCC Certificate:</b>                | CCC_2007010303228779 |
| <b>CSA Certificate:</b>                | CSA_1587291          |
| <b>cUR Certificate:</b>                | cUR_E244330          |
| <b>Declaration of Conformity - CE:</b> | 1SAD938500-0159      |

|                          |                          |
|--------------------------|--------------------------|
| <b>EAC Certificate:</b>  | EAC_RU_C-PL.ME77.B.01873 |
| <b>GOST Certificate:</b> | GOST_POCC_DE.AB76.D02256 |
| <b>RMRS Certificate:</b> | RMRS_12.04008.250        |
| <b>RoHS Information:</b> | 1SAA981040-4403          |
| <b>UR Certificate:</b>   | UR_E244330               |
| <b>VDE Certificate:</b>  | VDE_40019129             |

---

## Classifications

---

|                                    |                            |
|------------------------------------|----------------------------|
| <b>Object Classification Code:</b> | K                          |
| <b>E-number:</b>                   | 4005310                    |
| <b>ETIM 4.0:</b>                   | EC001437 - Switching relay |
| <b>ETIM 5.0:</b>                   | EC001437 - Switching relay |
| <b>UNSPSC:</b>                     | 39121500                   |

---

