


PRODUCT-DETAILS

ADI 3M

ADI 3M Insulated connector



General Information

Extended Product Type	ADI 3M
Product ID	2CGD000692A1000
EAN	7331980053797
Catalog Description	ADI 3M Insulated connector
Long Description	Insulated connector for compact fitting of ADI 300. The ADI 3M is sold as a separate unit where standard ADI 300 connectors are added separately.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85381000
Country of Origin	Sweden (SE)

Popular Downloads

Data Sheet, Technical Information	2CGC0036
-----------------------------------	----------

Dimensions

Product Net Width	37 mm
Product Net Height	170 mm
Product Net Depth /	95 mm

Length	
Product Net Weight	0.3 kg

Technical

Conventional Thermal Current (I_{the})	630 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V
Rated Peak Withstand Current (I_{pk})	37 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 34 kiloampere rms
Power Loss	at Rated Operating Conditions per Pole 44 W
Standards	IEC 61238-1
Degree of Protection	acc. to IEC 60529 IP2X

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

REACH Declaration	2CGC0049
RoHS Information	2CGC0040

Container Information

Package Level 1 Units	30 piece
Package Level 1 Width	194 mm
Package Level 1 Depth / Length	524 mm
Package Level 1 Height	215 mm
Package Level 1 Gross Weight	10.71 kg
Package Level 1 EAN	7331980053797

Classifications

ETIM 7	EC000001 - Busbar terminal
ETIM 8	EC000001 - Busbar terminal
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	5411223

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

