



## Earthing – in-/outdoor

### Earthing Device with connector clamp JKP 250 for earthing of screened elbow connectors 250 A EN 61230 $I_k=8,0 \text{ kA/1 s}$



Earthing Device JKP250-X1-JK23H

# Earthing – in-/outdoor

## Earthing Device type JKP250-X1-JK23H

according to EN 61230, max 8,0 kA/1 s

Earthing Device JKP250-X1-JK23H is designed for earthing and short circuiting of screened elbow connectors 250 A . **The system enables to applicate the device without touching the elbow connectors with your hands.**

Additional equipment: Voltage Detector TAG 200 BC, Operating Pole MGV-U, Gripper DSG 65-VF and cases.



No.	Type	Description	Weight kg
E 16 588 10	<b>JKP250-X1-JK23H</b>	50/3x0,75+0,75 Earthing Device	4,5
E 42 098 73	TAG 200 BC	Voltage Detector	0,3
E 16 529 07	MGV-U 24	Operating Pole 24 kV	1,0
E 16 529 09	MGV-U 36	Operating Pole 36 kV	1,1
E 16 529 34	DSG 65-VF	Gripper	0,7
E 16 590 49	DFO/JSKL1-J	Case for Earthing Device	0,5
E 16 528 76	DFO 117	Case for Operating Pole	0,4

MGV-U 24

DFO/JSKL1-J

DFO 117