



SLC ONE 360 R68-83 WH 705TED 927 IP44 36°

11.03.2021

SLC1120



Product description

One downlight for all applications! Tilts 30° in all directions (360°). For new and rehab projects. Can be mounted into insulation, up to the moisture barrier.

Quick and easy installation

We have always been thinking about electricians when developing our products. Focusing on solutions which is practical and easy for the installer. One 360° and OneSoft comes with a quick connector between the downlight and driver so you can easily detach the downlight from the driver. We also use quick connection boxes with strain relief and connection for tubes.

One downlight for indoor and outdoor use

We have created a downlight which is suitable for outdoor and indoor use. The downlight is not 100% water sealed, but it is resistant enough to be used outdoors (IP44).

Perfect for rehab projects

We created a downlight for all existing cut-out holes from 68-83 mm. This, combined with a low installation height of just 46 mm, makes this downlight perfect for replacing old halogen downlights. You can also install these downlights directly into the insulation.

SLC One360° for new and rehab projects

Can be mounted into insulation, up to the moisture barrier

No installation box required

Tilts 30° in all directions (360°)

Suitable for outside installation

Quick Connection

16 mm Cable/Tube connection




Technical data


Suitable for built-in mounting	Yes
Suitable for suspended mounting	No
Adjustability	Rotating and swivelling
With light source	Yes
Material housing	Aluminium

Suitable for wall mounting	No
Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
Lamp holder	None
Surface protection	Powder coating


Colour housing	White
Surface brushed	No
Nominal voltage	220 - 240 V
Type of control gear	LED operating device current-controlled
Dimming phase cut-off	Yes
Light distributor	Reflector
Beam angle	Medium beam 21-40°
Rated life time L80/B10 at 25 °C	50000 h
Protection class	II
Max. system power	8 W
Colour temperature	2700 - 2700 K
Luminous flux	705 - 705 lm
Power factor	0,9
Built-in width	67 mm
Built-in diameter	68 mm
Number of poles	3
Connectable conductor cross section	0,75 - 2,5 mm ²
Luminaire efficacy	75 lm/W
Strain relief	True
Beam angle (°)	36
Rotate (°)	30
Operating temperature	-10°C ~ +45°C
Cut-out hole (Ø: mm)	68-83
Dimmable	Yes
Dimming range	1-100%
GTIN	7070938061360
HS Code	94051040

Material cover	Plastic, transparent
Voltage type	AC/DC
LED nominal current at constant current	180 - 180 mA
Control gear included	Yes
Reflector	High-gloss
Light sharing	Symmetric
Light outlet	Direct
Degree of protection (IP)	IP44
Rated ambient temperature according to IEC	-10 - 45 °C
Colour of light	White
Colour rendering index CRI	90-100
Rated luminous flux according to IEC 62722-	705 lm
Outer diameter	90 mm
Built-in height/depth	46 mm
Type of wiring	Suitable for through wiring
Conductor cross section	0,35 mm ²
Connection type	Plug clamp
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index (CRI/Ra)	90
Tilt-able (°)	360
Exterior color	White
Can be installed directly into the insulation	True
Dimming method	Trailing edge
Type of control signal	Trailing Edge
Brand	SLC
Produced by	The Light Group






Flux 606 lm
 Maximum 1418.80 cd/klm
 Position C=0.00 G=0.00
 Efficiency: 100.00%
 Date: 10-08-2021
 Asymmetrical



Scandinavian Lighting Concept

SLC1120



8
kWh/1000h

