

Park LED luminaire

PARK LED 5000lm, opal PC ball 400mm, 3000K

Code: PARKLED5000KO400PC3

EAN: 8596099051051



Vlastnosti svítidla

Product category:	Luminaire for streets and places	Degree of protection (IP):	IP65
Mounting method:	Post-top	Color housing:	Black
Material housing:	Plastic	With connection cable:	Yes
Made in Czech republic:	Yes		

Světelný zdroj

Lamp type:	LED exchangeable	Effective luminous flux (lm):	4900
System power (W):	42	Luminaire efficacy (lm/W):	117
Color temperature (K):	3000	Color rendering index CRI:	80-89
Rated life time L70/B50 (h):	100000	With lamp:	Yes
Replaceability:	Replaceable light source by professional, replaceable ballast		

Optický systém

Optical system:	KO	Material cover:	Plastic, opal
-----------------	-----------	-----------------	----------------------

Rozměry

Diameter (mm):	400	Cable length (m):	0,2
Suitable for top end size (mm):	60	Weight (kg):	5

Elektrické vlastnosti

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	Type of wiring:	Ending
No dim function:	Yes		