

PRODUCT-DETAILS

3GAA082350-BSK

M3AA 80ME 4



General Information

Product ID	3GAA082350-BSK
ABB Type Designation	M3AA 80ME 4
Catalog Description	M3AA 80ME 4

Additional Information

ABB Type Designation	M3AA 80ME 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Country of Origin	China (CN) Finland (FI) Poland (PL)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.75 kW	1440 r/min	1.68 A	0.760	82.60 %	4.90 N·m	7.90
D	--	50 Hz	230 V	0.75 kW	1440 r/min	2.92 A	0.760	82.50 %	4.90 N·m	7.90
Y	--	50 Hz	380 V	0.75 kW	1431 r/min	1.70 A	0.800	82.50 %	5.00 N·m	7.40
D	--	50 Hz	220 V	0.75 kW	1431 r/min	2.93 A	0.800	82.50 %	5.00 N·m	7.40
Y	--	50 Hz	415 V	0.75 kW	1445 r/min	1.67 A	0.740	82.50 %	4.90 N·m	8.30
Y	--	60 Hz	460 V	0.75 kW	1748 r/min	1.48 A	0.740	85.50 %	4.00 N·m	9.50

Gross Weight	16.5 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 82.5 % Partial Load (75%) 82.1 % Partial Load (50%) 79.4 %
IE Class Data (60 Hz)	IE Class IE4 Full Load (100%) 85.5 % Partial Load (75%) 84.4 % Partial Load (50%) 81.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 80ME 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	13.5 kg
Product Type	3AA3__M3AA_IE3_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

