

PRODUCT-DETAILS

3GAA102550-BSK

M3AA 100LE 4



General Information

Product ID	3GAA102550-BSK
ABB Type Designation	M3AA 100LE 4
Catalog Description	M3AA 100LE 4

Additional Information

ABB Type Designation	M3AA 100LE 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6306-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	China (CN) Finland (FI) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	2.20 kW	1454 r/min	4.30 A	0.830	86.70 %	14.50 N-m	8.90
D	--	50 Hz	230 V	2.20 kW	1454 r/min	7.40 A	0.830	86.70 %	14.50 N-m	8.90
Y	--	50 Hz	380 V	2.20 kW	1448 r/min	4.40 A	0.840	86.70 %	14.50 N-m	8.10
D	--	50 Hz	220 V	2.20 kW	1448 r/min	7.60 A	0.840	86.70 %	14.50 N-m	8.10
Y	--	50 Hz	415 V	2.20 kW	1458 r/min	4.10 A	0.810	86.70 %	14.50 N-m	9.50
Y	--	60 Hz	460 V	2.20 kW	1760 r/min	3.80 A	0.810	89.50 %	11.90 N-m	10.20

Gross Weight	41 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.7 % Partial Load (75%) 87.0 % Partial Load (50%) 85.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.5 % Partial Load (75%) 89.2 % Partial Load (50%) 87.4 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 100LE 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	36 kg
Product Type	3AA3__M3AA_IE3_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain Shanghai, China Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

