



SLC Power Supply CV 24V 200W PWM Trailing Edge IP67

23/08/2022

S32099



Product description

200W power supply with built-in PWM dimmer. Dimmed with phase-cut/section. Mono. IP67 for outdoor use.

200W power supply with built-in PWM dimmer. Dimmed with phase-cut / section. Mono. Overload protection, short circuit and overheating. For 24V LED strips and other products with 24V operating voltage. Can be installed outside.

Technical data

Model	Static
Dimming phase cut-off	Yes
Suitable for constant voltage	Yes
Output current	2700 - 8300 mA
Degree of protection (IP)	IP67
Length	249 mm
Height	40 mm
Number of LED Output Channels	1
Input voltage (V)	220 - 240
Power factor	0,95
Operating temperature	-20°C ~ +45°C
Tc (°C)	80
Dimming interface	Trailing edge
Brand	SLC

Suitable for outdoor use	Yes
Housing	Metal housing
Output voltage	24 - 24 V
Output power	200 - 200 W
Protection class	I
Width	72 mm
Output type	Constant voltage (CV)
Mono	Yes
Frequency range (Hz)	50 - 60
Inrush Current (A)	65
Expected lifetime (Hours) (Ta 45°C)	50000
Dimming method	Pulse Width Modulation (PWM)
Dimming range	1-100%
Produced by	The Light Group

