



SLC DALI DT8 RGB/RGBW Wall Panel Touch MCU/SLAVE

23/08/2022

S52033

Product description

Adjust the color and light level of a channel or broadcast. DALI master for use without central DALI bus. Can also be set up as a slave with PSU.

Adjust the color and light level of a channel or broadcast. DALI master for use without central DALI bus. Can also be set up as a slave with PSU. 1 channel with the possibility to store up to 4 individual scenarios.

Technical data

Model	Static	Suitable for outdoor use	No
Operating method	DALI	Number of colour channels	4
Programmable	Yes	Housing	Other
Surface-mounted	Yes	Built-in	Yes
DIN rail mounting	No	Input voltage	100 - 240 V
Degree of protection (IP)	IP20	Protection class	II
Length	86 mm	Width	86 mm
Height	29 mm	Mono	No
Tunable White	No	RGB	Yes
RGBW	Yes	Operating temperature	0°C ~ +40°C
Expected lifetime (Hours) (Ta 25°C)	110000	Expected lifetime (Hours) (Ta 45°C)	50000
Number of DALI-address	1	DALI-bus power consumption (mA)	15
DALI bus output power (mA)	100	DALI version	DALI
DALI Type	DT8	DALI DT8 Color Management Protocol	RGBWAF
Dimming interface	DALI DT8		





GTIN	7070938060592
-------------	---------------

HS Code	85371098
----------------	----------

Brand	SLC
--------------	-----

Produced by	The Light Group
--------------------	-----------------
