

## Pax Flex I 5/550, pivoting

|              |               |
|--------------|---------------|
| Cat. Part    | 25-2018       |
| Number       |               |
| EAN 13       | 7391477520188 |
| SE EL (SEG)  | 9411192       |
| SE VVS (RSK) | 8754377       |
| NO EL (EFO)  | 5800656       |
| NO VVS (NRF) | 8245352       |
| FI VVS (LVI) | 5280886       |
| DK EL (DB)   | 2006734       |
| DK VVS (VVS) | 331165314     |
| FI EL (SNRO) | 8133293       |

**Flex I, pivoting arms on small space**


- Pivoting arms in a small area

**Flex I, 5 arms 560 mm individually pivotable.  
On/Off function. 50W. Chrome-plated steel.**

### Technical data

|                                       |          |
|---------------------------------------|----------|
| Installation type, wall, ceiling et.c | Wall     |
| Max watt(W)                           | 50       |
| Supply Voltage (12V-400V)             | 230V AC  |
| Electrical Supply Phase               | 1-Phase  |
| Insulation Class                      | II       |
| Protection ( IP )                     | IP 44    |
| Heat Output, electrical products (W)  | 50       |
| Unpackaged Product Width (mm)         | 560      |
| Unpackaged Product Height (mm)        | 600      |
| Unpackaged Product Depth (mm)         | 112      |
| Material                              | Steel    |
| Etim Code                             | EC003624 |

### Måttskiss



Flex I has individually pivoting arms that you can move as you wish, either to maximise your drying capability or to make Flex I as compact as possible. The tubes are straight, which makes it easy to hang up and take down your towels. You can order your Flex I in several configurations. Choose anything from two to six individually pivoting arms to 180°, meaning you can have it set both on the right and left.

The chrome-plated steel construction is very stable with metal brackets and the effect is 50W. The towel warmer can be mounted right or left-hand.

Flex I 5/550 is also available with Momento II™ timer function.



Cat 8340-5