

PRODUCT-DETAILS

EH04-11N

EH04-11N Auxiliary Contact



General Information

| | |
|-----------------------|---|
| Extended Product Type | EH04-11N |
| Product ID | 1SAE901901R1011 |
| EAN | 4013614527616 |
| Catalog Description | EH04-11N Auxiliary Contact |
| Long Description | The EH04 are auxiliary contact blocks which can be used in combination with all the new ESB..N and EN..N installation contactors. These devices are available in 2 different contact configurations and no tool is needed for their assembling. |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85369010 |

Popular Downloads

| | |
|--------------------------|-----------------|
| Instructions and Manuals | 2CDC103043M6801 |
|--------------------------|-----------------|

Dimensions

| | |
|----------------------------|-------|
| Product Net Width | 9 mm |
| Product Net Depth / Length | 65 mm |

| | |
|--------------------|---------|
| Product Net Height | 85 mm |
| Product Net Weight | 0.04 kg |

Technical

| | |
|---|---|
| Rated Operational Voltage | Auxiliary Circuit 500 V AC |
| Rated Frequency (f) | Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz |
| Rated Impulse Withstand Voltage (U_{imp}) | Auxiliary Circuit 4 kV |
| Rated Insulation Voltage (U_i) | 500 V |
| Number of Poles | 2 |
| Degree of Protection | IP20 |
| Tightening Torque | Auxiliary Circuit 0.9 N·m |
| Wire Stripping Length | Auxiliary Circuit, Top Terminals (1x 1.5) 7 mm Auxiliary Circuit, Top Terminals (1x 2.5 ... 4) 17 mm Auxiliary Circuit, Top Terminals (2x 1.5) 17 mm Auxiliary Circuit, Bottom Terminals (1x 1.5) 7 mm Auxiliary Circuit, Bottom Terminals (1x 2.5 ... 4) 9 mm Auxiliary Circuit, Bottom Terminals (2x 1.5) 9 mm |
| Recommended Screw Driver | Auxiliary Circuit Pozidriv 1 |
| Standards | IEC/EN 60947-5-1 |
| Number of Auxiliary Contacts NC | 1 |
| Number of Auxiliary Contacts NO | 1 |
| Number of Main Contacts NC | 0 |
| Number of Main Contacts NO | 0 |
| Product Name | Auxiliary Contact |
| Suitable For | ESB16..N ESB20..N ESB25..N ESB40..N ESB63..N EN20..N EN25..N EN40..N ESB100..N |
| Suitable for Product Class | Installation Contactors |

Technical UL/CSA

| | |
|--|---------------------------|
| Maximum Operating Voltage UL/CSA | 600 V AC |
| Connecting Capacity Auxiliary Circuit UL/CSA | Stranded 18-12 AWG |
| Tightening Torque UL/CSA | Auxiliary Circuit 8 in·lb |

Environmental

| | |
|--|--|
| Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +80 °C |
| Conventional Free-air Thermal Current (I_{th}) | Auxiliary Circuit 6 A |
| Maximum Operating | 2000 m |

Altitude Permissible

| | |
|--|-----------------------------------|
| Resistance to Shock acc. to IEC 60068-2-27 | 11 ms Pulse 15g |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 3 ... 150 Hz |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|----------------------------------|---------------------|
| ABS Certificate | 1SAA920000-0101 |
| CB Certificate | 1SAA920006-2001 |
| CQC Certificate | CQC2017010304980330 |
| cULus Certificate | cUL_E191658 |
| Declaration of Conformity - CCC | 2020980305001265 |
| Declaration of Conformity - CE | 1SAD938506-0302 |
| Declaration of Conformity - UKCA | 1SAD938501-1302 |
| DNV Certificate | 1SAA920000-0306 |
| EAC Certificate | 1SAA920002-2701 |
| Instructions and Manuals | 2CDC103043M6801 |
| RINA Certificate | 1SAA920000-0801 |
| RoHS Information | 1SAD938506-0302 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 87 mm |
| Package Level 1 Depth / Length | 18 mm |
| Package Level 1 Height | 69.5 mm |
| Package Level 1 Gross Weight | 0.05 kg |
| Package Level 1 EAN | 4013614527814 |
| Package Level 1 Units | 1 piece |

Classifications

| | |
|----------------------------|------------------------------------|
| Object Classification Code | K |
| ETIM 5 | EC000041 - Auxiliary contact block |
| ETIM 6 | EC000041 - Auxiliary contact block |
| ETIM 7 | EC000041 - Auxiliary contact block |
| ETIM 8 | EC000041 - Auxiliary contact block |
| eClass | V11.0 : 27371302 |
| UNSPSC | 39121522 |
| E-Number (Finland) | 3707816 |
| E-Number (Sweden) | 3210569 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Installation Contactors Accessories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Installation Contactors Accessories

