



EN ISO 20344:2011



ATLANTIDA  
**ELDORADO**  
80117-00L

**S3 HRO HI SRC**

**Size:** 38-48  
**Weight:** 770 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Engineering, Farming and  
Gardening



## FEATURES

### UPPER

Greased Nubuk Dakar Leather  
Hydro 1,8-2,0 mm  
Reflex insert

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

### TYPE

Ankle boot

### SOLE

#### PU-RUBBER VIBRAM-HRO

Sole with anti-wear scaff cap.  
Outsole in VIBRAM rubber,  
resistant to 300° C by contact  
(HRO), to acids and oils. Design  
with self-cleaning outsole, with  
Antislip standard.

## TECHNOLOGIES

### Removable Insole

**climaction fit** 337

Removable anatomic and ergonomic  
insole. Absorbent and transpiring  
open-cell foam support. Keeps feet  
fresh. Specifically-designed  
thermoforming for exceptional  
comfort.



### Protection elements

**RESISTANT TO 3.0 mm. NAILS** *fibercap sxt*

Composite toecap with fiberglass.  
Resistant to over 200J. Non metal  
perforation resistant insert to over  
1100 N with a 3.0 mm truncated cone  
nail. Protection over the entire sole of  
the foot. Flexible and comfortable



### Lateral stability

**dynamic control**  
technology

Ergonomic rigid structure. It  
accommodates the heel, adjusting the  
foot support and control of the ankle  
in sideways movements. The plastic  
material increases protection of the  
ankle against sharp or pointy objects.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.




### Electrical features

**WED**

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,  
ensuring proven anti-static properties  
of the footwear over time.



### Other

**DUALMICRO**

Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.



## SRC (SRA+SRB)



		SOLE 80 PU - RUBBER
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE 1°) ≥0.28	<b>0.43</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE 1°) ≥0.13	<b>0.19</b>

EN ISO 20344:2011