

PRODUCT-DETAILS

# OTDC25F2

## OTDC25F2 DC Switch-disconnector




---

### General Information

Extended Product Type	OTDC25F2
Product ID	1SCA121455R1001
EAN	6417019526102
Catalog Description	OTDC25F2 DC Switch-disconnector
Long Description	OTDC25F2 DC Switch-disconnector, Terminal bolt kit included, Handle and shaft need to be ordered separately, Base mounting, IEC 660 VDC 25 A single circuit, IEC 1000 VDC 16 A single circuit

---

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Information	NA
REACH Declaration	1SCC301240D0201
RoHS Information	1SCC301239D0201

---

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Estonia (EE)

## Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301079M0206
Mechanical Drawings	OTDC16-32F2.igs 1SCC301970F0001 1SCC301971F0001

## Dimensions

Product Frame Size	XS
Product Net Width	52.5 mm 2.1 in
Product Net Height	89 mm 3.5 in
Product Net Depth / Length	66.2 mm 2.6 in
Product Net Weight	0.1 kg 0.3 lb

## Technical

Rated Operational Current DC-21B ( $I_e$ )	(660 V) 25 A (1000 V) 16 A
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40\text{ }^\circ\text{C}$ 32 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 32 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(1000 V DC) 0.8 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	(1000 V DC) 0.8 kA for 1 s 0.8 kA
Power Loss	at Rated Operating Conditions per Pole 0.3 W
Pollution Degree	3
Handle Color	Black
Handle Type	Knob handle
Positive Opening Operation Torque (Direct Opening Action)	0.4 ... 0.8 N·m
Shaft Diameter	6 mm 0.24 in
Switches Operating Mechanism	Mechanism on Top of the Switch
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front Operated
Standards	IEC 60947-1, -3
Special Functions	No
Mounting Type	Base mounting, DIN-rail mounting

Number of Circuits	1
Number of Poles	2
Cable Cross-Section	2.5 ... 16 mm <sup>2</sup>
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Utilization	Photovoltaic
Utilization Category	Switching of resistive loads, including moderate overloads - occasional actuation (DC-21B)

## Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	NA

## Certificates and Declarations (Document Number)

CCC Certificate	CQC2012010302579872
Declaration of Conformity - CE	1SCC301192D2704
Declaration of Conformity - UKCA	1SCC301313D0201
DNV GL Certificate	1SCC301231D0201
Environmental Information	NA
Instructions and Manuals	1SCC301079M0206
REACH Declaration	1SCC301240D0201
RoHS Information	1SCC301239D0201

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	100 mm 3.9 in
Package Level 1 Depth / Length	64 mm 2.5 in
Package Level 1 Height	100 mm 3.9 in
Package Level 1 Gross Weight	0.2 kg 0.4 lb
Package Level 1 EAN	6417019526102

## Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601354
E-Number (Sweden)	3134019

---

## Categories

---

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

