


PRODUCT-DETAILS

# OT63FT4N2/B50

## OT63FT4N2/B50 SWITCH-DISCONNECTOR




---

### General Information

Extended Product Type	OT63FT4N2/B50
Product ID	1SCA126085R1001
EAN	6417019560847
Catalog Description	OT63FT4N2/B50 SWITCH-DISCONNECTOR
Long Description	OT63FT4N2/B50 SWITCH-DISCONNECTOR

---

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Information	1SCC301263D0201
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

---

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

---

### Popular Downloads

Data Sheet, Technical Information	No documentation needed
Instructions and Manuals	1SCC301063M0006
Mechanical Drawings	1SCC301456F0001 1SCC301455F0001 OT63-80FT4N2

## Dimensions

Product Net Width	65 mm
Product Net Height	72 mm
Product Net Depth / Length	69 mm
Product Net Weight	14.6 kg

## Technical

Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 63 A (500 V) 45 A (690 V) 20 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 11 kW (400 ... 415 V) 22 kW (500 V) 22 kW (690 V) 15 kW
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 63 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 2.1 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 1.5 kA
Power Loss	at Rated Operating Conditions per Pole 2.8 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Standards	IEC 60947-3 / UL 508 / CSA C22.2 No. 14
Number of Poles	4
Cable Cross-Section	Cu 1.5 ... 35 mm <sup>2</sup>
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 2 N·m
Mechanical Durability	20000
Lock Type	No

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	60 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 7.5 Hp (440 ... 480 V AC) Single Phase 15 Hp (550 ... 600 V AC) Single Phase 15 Hp (220 ... 240 V AC) Three Phase 15 Hp (440 ... 480 V AC) Three Phase 30 Hp (550 ... 600 V AC) Three Phase 30 Hp
Tightening Torque	acc. IEC 60947-1 2 N·m

---

## Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	1SCC301263D0201

---

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301167D2704
Environmental Information	1SCC301263D0201
Instructions and Manuals	1SCC301063M0006
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
UL Certificate	cULus certificate OT16-80

---

## Container Information

Package Level 1 Units	box 50 piece
Package Level 1 Width	275 mm
Package Level 1 Depth / Length	433 mm
Package Level 1 Height	160 mm
Package Level 1 Gross Weight	15.5 kg
Package Level 1 EAN	6417019560847

---

## Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

