




EN ISO 20345:2011 


RESOLUTE
FORZA BOA®
43460-02L

S3 SRC *CI AVAILABLE

Size: 36-48
Weight: 610 gr.

Fit: 11

Working Environment:
Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas



FEATURES

UPPER
MicroFiber Suede 1,6-1,8 mm
MicroFiber Suede with Scratch Bumper 1,8-2,0 mm
MicroFiber Suede 1,8-2,0 mm

LINING
3D Green Air 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Qrs01

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
Textile resistant to 3.0 mm nail


SOLE
PU / PU ESD-PLUS SRC
Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

Boa® lace length
L6 - 85cm

TECHNOLOGIES

Removable Insole
QRSOI
Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use

Protection elements
RESISTANT TO 3.0 mm NAILS **fibercap sxt**
Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

SRC (SRA+SRB)

SOLE 43
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (CONTACT ANGLE °) ≥ 0.28	0.39
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (CONTACT ANGLE °) ≥ 0.13	0.24

EN ISO 20344:2011

Lateral stability
dynamic HC control technology
Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability
STABIL•ACTIVE
Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
ESD
ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other
D3O **PROGRESSIVE CUSHIONING AND ADAPTIVE STABILITY**
D3O materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.

