

Switching Power Supplies Constant Current Dimmable 3G



Constant current power supplies 3G can be dimmed with standard AC phase-cut dimmers (triac). With MM-sign and F-sign. Can be mounted on inflammable subsurface. Noiseless – without fan.

TECHNICAL DATA

Frequency range	50/60 Hz
-----------------	----------

PRODUCT TYPES

order code	output current	output voltage	power	MM	power source	dimensions (l x w x h)	weight
L5233012D3G	300 mA	21-40 VDC	12 Watt	yes	220- 240 VAC	115 x 39 x 22 mm	0,08 kg
L5233509D3G	350 mA	11-26 VDC	9 Watt	yes	220- 240 VAC	115 x 39 x 22 mm	0,08 kg
L5233512D3G	350 mA	18-35 VDC	12 Watt	yes	220- 240 VAC	115 x 39 x 22 mm	0,08 kg
L5233520D3G	350 mA	28-56 VDC	20 Watt	yes	220- 240 VAC	127 x 44 x 28 mm	0,12 kg
L5235012D3G	500 mA	12-24 VDC	12 Watt	yes	220- 240 VAC	115 x 39 x 22 mm	0,08 kg
L5235022D3G	500 mA	20-44 VDC	22 Watt	yes	220- 240 VAC	127 x 44 x 28 mm	0,12 kg
L5237009D3G	700 mA	6-13 VDC	9 Watt	yes	220- 240 VAC	115 x 39 x 22 mm	0,08 kg
L5237012D3G	700 mA	9-18 VDC	12 Watt	yes	220- 240 VAC	115 x 39 x 22 mm	0,08 kg

order code	output current	output voltage	power	MM	power source	dimensions (l x w x h)	weight
L5237022D3G	700 mA	14-32	22	yes	220-	127 x 44 x 28	0,12
		VDC	Watt		240	mm	kg
					VAC		
L5231022D3G	1050 mA	9-20	22	yes	220-	127 x 44 x 28	0,12
		VDC	Watt		240	mm	kg
					VAC		

MEMBER OF THE PROLED GROUP